FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ELEVATION CERTIFICATE

O M B No 3067-00 Expres May 31-19

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances. to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or COM - Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME	POLICY NUMBER
HANITSCH	ļ
STREET ADDRESS (Including Apt., Unit, Suite and/or Bidg, Number) OR PO, ROUTE AND BOX NUMBER	COMPANY NAIC NUMBER
20240 CARRIAGE CT	
OTHER DESCRIPTION (Lol and Block Numbers. elc.)	
LAT ON BLOOK & DULLE HEDDER HALL BULLETERS I AND	

LOT 47, BLOCK A, PHASE 4, RIVERWOODS	PLANTATION P.B. 37, P. 90	1999 LEE CO.
CITY	STATE	ZIP CODE
ESTERO	<u> </u>	33908

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions).

Permit # 19970/626

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4 DATE OF FIRM INDEX	5. FIRM ZONE	6 BASE FLOOD ELEVATION
125124	0455	B	9-20-96	A 14	EL II

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): KINGVD '29 Other (describe on back 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level ...5.
- 2(a), FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of L1.11/出后 feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is feet above or below [] (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below conece one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: Yes X No. (See Instructions on Page 4)
- 5. The reference level elevation is based on: X actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: <u>11.2</u> feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

2. Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner or downer's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-It the certifier is unable to certify to breakaway/non-breakaway work enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Featurets), then list the Featurets included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

and the second states and the second states and	and the second	Yan ta a she ta ta ta ta ta		
CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)			
MARK O. ALLEN	3553			
TITLE	COMPANY NAME			
LAND SURVEYOR	MARK O, ALLEN LAND S	URVEYOR		
ADORESS	СІТҮ	STATE ZP		
26751 OLD 41 RD. S.E.	BONITA SPRINGS	FLA. 33923		
SIGNATURE SITE ST. 7.97	DATE 3+6-97	PHONE (813) 992'-8900		
Coples should be made of this Certificate for: 1)	community official, 2) insurance agent/co	ompany, and 3) building owner.		
COMMENTS: ELEVATIONS BASED	ON CHES BOUCHMARK DI	3K STAMPED W 244"		
· · · · · · · · · · · · · · · · · · ·				
······································				
······································				



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.