#39	9798
199	800052

KIH

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M B. No 3067 0077 Expires May 31 1997

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances. to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMP Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE POLICY NUMBER	
BUILDING OWNER'S NAME Herbert Campfield		
STREET ADDRESS (Including Apt., Unit, Suite and/or Bidg. Number) OR P.O. ROUTE AND BOX NUMBER 4671 Slash Pinc Will West, Estera, Ela.	COMPANY NAIC NUMBER	
OTHER DESCRIPTION (Lot and Block Numbers, etc.) Lot 18, BIK B, Riverwoods, Phase 4, P.B. 37, Pgs. 98:99	, Lee G. F.A.	
city Estero Fla	E ZIP CODE	
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMAT	TION	
Provide the following from the proper FIRM (See Instructions):		

1. COMMUNITY NUMBER2. PANEL NUMBER3. SUFFIX4. DATE OF FIRM INDEX5. FIRM ZONE6. BASE FLOOD ELEVATION
(in AO Zones, use depth)1251240455B9-19-84A-1411.00

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): ONGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate

the community's BFE:

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level _____.
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of LLL14.13 feet NGVD (or other FIRM datum-see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of ______ feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ______ feet above ____ or below ____ (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is ______ feet above _____ or below _____ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? _____ Yes ____ No ____ Unknown
- 4. Elevation reference mark used appears on FIRM: 🛄 Yes 🖾 No (See Instructions on Page 4)
- 5. The reference level elevation is based on: Z actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: <u>11</u> is teet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

- 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: ______ feet NGVD (or other FIRM datum-see Section B, Item 7).
- 2. Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE),V1-V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAM	E			LICENSE NUMB	ER (or Affix S	eal)	•	
MAR	K O. ALLEN		ւնքը։ Կես - արտեր	3553				
TITLE			COMPAN	IY NAME	_ >			
LAN	D SURVEYOR		MARI	K O. ALLEN	LAND S	URVEYOR		
ADDRESS	51.950 x1/81	8. S.E.	7 CITY BON	ITA SPRINGS		S F	LA.	ZIP
SIGNATURE	MIII.	1		DATE		PHONE (813)	992-8900	
Copies should	i be made of this Ce	ertificate for	: 1) community o	fficial, 2) insuranc	e agent/co	ompany, and 3)	building owner	ſ
COMMENTS:	Elevations	based	on C!GS	benchmark	. disk	stampec	1 ." W.240	1.1965
COMMENTS:	Elevations	based	on C!GS	benchmark	¹ . disK	stampec	1 <u>" 11-240</u>	1.1965
COMMENTS:	Elevations	based	on C!65	benchmark	¹ . disK	stampec	<u>" w/ 240</u>	1965
COMMENTS:	Elevations	based	on C!65	benchmarK	^{r.} disk	stampec	1 <u>" W 240</u>	1965
COMMENTS:	Elevations	based	on C!G5	benchmark	^{c.} disk	stampec	1 <u>" W 240</u>	1965
COMMENTS:	Elevations	based	on C!GS	benchmark	i disk	stampec	<u>" w/ 244</u>	+ 196 <



Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.

1

11

ς