

12/27/2023 12:25:55 PM Sabrina H:_Project\22\2213_EsteroRiverPedBridge\Structures\KeySheet.dgn

INDEX OF STRUCTURE PLANS

SHEET NO.	SHEET DESCRIPTION
1	KEY SHEET
2	SUMMARY OF STRUCTURE QUANTITIES
3 - 4	GENERAL NOTES
5	TRUSS CONFIGURATION
6	PROJECT LOCATION
7 - 8	SLOPE PROTECTION DETAILS
9 - 10	PLAN & ELEVATION
11	TYPICAL SECTION
12	SUPERSTRUCTURE DETAILS
13	BRIDGE HYDRAULIC RECOMMENDATIONS
14	REPORT OF CORE BORINGS
15	FOUNDATION LAYOUT
16	PILE DATA TABLE
17	PIER 1 PLAN & ELEVATION
18	PIER 2 PLAN & ELEVATION
19 - 21	PIER DETAILS
22	FOOTING DETAILS
23	REINFORCING BAR LIST
24	BOARDWALK TYPICAL SECTION
25	BOARDWALK FRAMING PLAN
26	ABUTMENT END TRANSITION
27	ABUTMENT END WALL ELEVATION

STANDARD PLANS FOR ROAD AND BRIDGE CONSTRUCTION	
400-011	GRAVITY WALL

LOCATION OF PROJECT

8791 CORKSCREW ROAD
ESTERO, FL 33928



GOVERNING STANDARD PLANS:

Florida Department of Transportation, FY 2023-24 Standard Plans for Road and Bridge Construction and applicable Interim Revisions (IRs).

Standard Plans for Road and Bridge Construction and associated IRs are available at the following website: <http://www.fdot.gov/design/standardplans>

GOVERNING STANDARD SPECIFICATIONS:

Florida Department of Transportation, FY 2023-24 Standard Specifications for Road and Bridge Construction at the following website: <http://www.dot.state.fl.us/programmanagement/Implemented/SpecBooks>


VILLAGE OF ESTERO

CONTRACT PLANS

ESTERO ON THE RIVER
PEDESTRIAN BRIDGE
VOE CONTRACT NO. 2022-41

STRUCTURE PLANS

PRELIMINARY
NOT FOR CONSTRUCTION



LOCATION OF PROJECT

THIS ITEM HAS BEEN DIGITALLY
SIGNED AND SEALED BY

ON THE DATE ADJACENT TO THE SEAL

PRINTED COPIES OF THIS DOCUMENT ARE
NOT CONSIDERED SIGNED AND SEALED
AND THE SIGNATURE MUST BE VERIFIED
ON ANY ELECTRONIC COPIES.

STRUCTURE PLANS
ENGINEER OF RECORD:

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BLVD.
SUITE 200
FORT MYERS, FL 33901

VILLAGE OF ESTERO
PROJECT MANAGER:

DAVID WILLEMS, P.E.

100% SUBMITTAL
DECEMBER 2023

CONTRACT NO.	FISCAL YEAR	SHEET NO.
EC2022-41	24	1

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:18 PM Sabrina H:_Project\22\2213_EsteroRiverPedBridge\Structures\SummaryOfStructuresQuantities.dgn

SUMMARY OF STRUCTURE QUANTITIES										
SECTION	PAY ITEM NO.	PAY ITEM DESCRIPTION	LOCATION	UNIT	QUANTITY		TOTAL		DESIGN NOTES	CONSTRUCTION REMARKS
					P	F	P	F		
SLOPE PROTECTION	530-3-3	RIPRAP- RUBBLE , BANK AND SHORE	END WALL 1	TN	119.1		477.1			
			PIER 1		108.4					
			PIER 2		108.4					
			END WALL 2		141.2					
	530-74	BEDDING STONE	END WALL 1	TN	41.8		373.6			
			BOARDWALK NO. 1		73.4					
			PIER 1		40.4					
			PIER 2		40.4					
			BOARDWALK NO. 2		128.0					
FOUNDATION			END WALL 2		49.6					
	455-34-2	PRESTRESSED CONCRETE PILING, 14" SQ.	PIER 1	LF	150		300			
			PIER 2		150					
	455-143-2	TEST PILES-PRESTRESSED CONCRETE, 14" SQ	PIER 1	LF	60		120			
			PIER 2		60					
SUBSTRUCTURE	400-4-5	CONCRETE CLASS IV, SUBSTRUCTURE	PIER 1	CY	11.9		24.9			
			PIER 2		13.0					
	415-1-5	REINFORCING STEEL - BRIDGE SUBSTRUCTURE	PIER 1	LB	2496		5263			
			PIER 2		2767					
	999-01	ANCHOR BOLT ASSEMBLY	PIER 1	EA	4		8			
			PIER 2		4					
SUPERSTRUCTURE	400-2-4	CONCRETE CLASS II, BRIDGE SUPERSTRUCTURE	STEEL TRUSS	CY	24.8		24.8			
	400-148	PLAIN NEOPRENE BEARING PADS	STEEL TRUSS	CF	0.2		0.2			
	415-1-4	REINFORCING STEEL - BRIDGE SUPERSTRUCTURE	STEEL TRUSS	LB	5467		5467			
	460-7	PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE	STEEL TRUSS	LS	1		1			
	515-2-356	PEDESTRIAN/BICYCLE RAILING, ALUMINUM ONLY, 42" STEEL CABLE SYSTEM	STEEL TRUSS	LF	268		268			
SPECIAL FEATURES	104-10-3	SEDIMENT BARRIER	CHANNEL BANKS	LF	647		647			
	104-11	FLOATING TURBIDITY BARRIER	PIER 2	LF	95		95			
	110-1-1	CLEARING & GRUBBING	PROJECT SITE	AC	0.32		0.32			
	400-0-11	CONCRETE CLASS NS, GRAVITY WALL INDEX 400-011	END WALL 1	CY	8.1		20.8			
			END WALL 2		12.7					
	455-2-12	TREATED TIMBER PILING FOR PEDESTRIAN BOARDWALK	BOARDWALK	LF	1020		1020			
	470-1	TREATED TIMBER, STRUCTURAL	BOARDWALK	MB	9.8		9.8			

PAY ITEM NOTES:

1. PAY ITEM 455-2-12 INCLUDES ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS NECESSARY TO SHIP AND INSTALL TIMBER PILES FOR THE BOARDWALK. QUANTITY IS BASED ON ORDER PILE LENGTH REPORTED ON THE PILE DATA TABLE.
2. PAY ITEM 460-7 INCLUDES ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS NECESSARY TO FABRICATE, SHIP, ASSEMBLE, AND INSTALL THE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE. INCLUDES COMPONENTS FOR BOARDWALK ATTACHMENT TO BEGIN AND END BRIDGE.
3. PAY ITEM 470-1 INCLUDES ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS NECESSARY FOR THE CONSTRUCTION OF THE TIMBER BOARDWALK, TIMBER RAILINGS ALONG THE END WALLS, AND RELATED COMPONENTS, EXCLUDING TIMBER PILING. INCLUDES ALL HARDWARE, STRAPS, BOLTS, AND SCREWS. TIMBER MATERIALS AND CONSTRUCTION PER FDOT STANDARD SPECIFICATIONS SECTION 470.
4. PAY ITEM 515-2-356 INCLUDES ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS NECESSARY TO FABRICATE, SHIP, ASSEMBLE, AND INSTALL THE ALUMINUM PEDESTRIAN RAILING WITH STEEL CABLE SYSTEM. THE STEEL TRUSS BRIDGE FABRICATOR SHALL SUBMIT SHOP DRAWING OF PROPOSED RAILING SYSTEM IN ACCORDANCE TO PLAN PROVISIONS AND GENERAL NOTES.
5. PAY ITEM 999-01 INCLUDES ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS NECESSARY TO INSTALL THE ANCHOR BOLTS FOR THE STEEL TRUSS CONNECTION TO THE PIER CAPS. INCLUDES TWO NUTS AND ONE WASHER PER BOLT.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION						SUMMARY OF STRUCTURE QUANTITIES		
		<div>PRELIMINARY NOT FOR CONSTRUCTION</div>						ROAD NO.		COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.
								-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		2

PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:18 PM Sabrina H:_Project22\2213_EsteroRiverPedBridge\Structures\GeneralNotes.dgn

GENERAL NOTES

- A. DESIGN SPECIFICATIONS
- AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO) LRFD GUIDE SPECIFICATIONS FOR THE DESIGN OF PEDESTRIAN BRIDGES (2009).
 - FDOT STRUCTURES MANUAL DATED JANUARY 2023 AND SUBSEQUENT STRUCTURES DESIGN BULLETINS.
 - AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO) LOAD AND RESISTANCE FACTOR (LRFD) BRIDGE DESIGN SPECIFICATIONS, 9TH EDITION (2020), AND ALL SUBSEQUENT INTERIMS.
 - FDOT DESIGN MANUAL DATED JANUARY, 2023 AND SUBSEQUENT ROADWAY DESIGN BULLETINS.
- B. GOVERNING STANDARDS AND CONSTRUCTION SPECIFICATIONS
- FLORIDA DEPARTMENT OF TRANSPORTATION, FY 2023-24 STANDARD PLANS AND REVISED INDEX DRAWINGS AS APPENDED HEREIN, AND FY 2023-24 STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, AS AMENDED BY CONTRACT DOCUMENTS.
- C. VERTICAL DATUM
- NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD 88)
- D. ENVIRONMENT

BRIDGE NUMBER	SUPERSTRUCTURE	SUBSTRUCTURE	
		CONCRETE	STEEL
ESTERO RIVER BRIDGE	SLIGHTLY	MODERATELY	MODERATELY

- E. DESIGN METHODOLOGY
- LOAD AND RESISTANCE FACTOR DESIGN (LRFD) METHOD USING STRENGTH, SERVICE, AND FATIGUE LIMIT STATES.
- F. DESIGN LOADINGS
- PEDESTRIAN LIVE LOAD: 90 PSF
VEHICULAR LIVE LOAD: 4000 LB MAINTENANCE VEHICLE
 - DEAD LOADS:
TIMBER RAILING: 35 PLF
REINFORCED CONCRETE: 150 PCF
STRUCTURAL STEEL: 490 PCF
 - WIND LOAD: WIND LOADS SHALL BE COMPUTED IN ACCORDANCE WITH STRUCTURES DESIGN GUIDELINES SECTION 10.5 FOR PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGES.
 - THERMAL LOAD: CONCRETE COEFFICIENT OF THERMAL EXPANSION: 6.0×10^{-6} / °F
STEEL COEFFICIENT OF THERMAL EXPANSION: 6.5×10^{-6} / °F

SUPERSTRUCTURE MATERIAL	TEMPERATURE (°F)			
	MEAN	HIGH	LOW	RANGE
CONCRETE DECK ON STEEL TRUSS	70	110	30	80

- UTILITIES: NO ALLOWANCE FOR UTILITY LOADS HAS BEEN INCLUDED IN DESIGN.
- CONSTRUCTION LOADS: THE CONTRACTOR SHALL SUBMIT ALL TEMPORARY LOADING FOR REVIEW AND APPROVAL.
- NO ALLOWANCE FOR FUTURE WEARING SURFACE HAS BEEN INCLUDED IN THE DESIGN.

- G. MATERIALS
- REINFORCING STEEL: GRADE 60 CARBON STEEL PER SPECIFICATIONS SECTION 931.
 - CONCRETE:

CONCRETE CLASS	MIN. 28-DAY COMPRESSIVE STRENGTH (PSI)	LOCATION OF CONCRETE IN STRUCTURE
II (BRIDGE DECK)	4500	C.I.P. BRIDGE DECK
IV	5500	C.I.P. SUBSTRUCTURE, ABUTMENTS
V (SPECIAL)	6000	PRESTRESSED CONCRETE PILES

3. CONCRETE COVER:


CAST-IN-PLACE BRIDGE DECK	2"
CAST-IN-PLACE SUBSTRUCTURE (CAST AGAINST EARTH)	4"
CAST-IN-PLACE SUBSTRUCTURE (FORMED SURFACES)	3"
CAST-IN-PLACE BEAM PEDESTAL	2"

CONCRETE COVER DIMENSIONS SHOWN IN THE PLANS DO NOT INCLUDE PLACEMENT AND FABRICATION TOLERANCES UNLESS SHOWN AS "MINIMUM COVER". SEE SPECIFICATIONS SECTION 415 FOR ALLOWABLE TOLERANCES. ALL DIMENSIONS PERTAINING TO THE LOCATION OF REINFORCING STEEL ARE TO CENTERLINE OF BAR EXCEPT WHERE CLEAR DIMENSION IS NOTED TO FACE OF CONCRETE.

4. STEEL TRUSS ANCHOR BOLTS
- ANCHOR BOLTS, NUTS, AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM F2329.
 - ALL ANCHOR BOLTS SHALL BE 1"x18" L-BOLTS, ASTM F1554 GRADE 105, UNLESS OTHERWISE NOTED.
 - ALL NUTS SHALL BE ASTM A563 GRADE A HEAVY HEX NUTS, UNLESS OTHERWISE NOTED.
 - ALL WASHERS SHALL BE ASTM F436 TYPE 1, UNLESS OTHERWISE NOTED. PROVIDE WASHERS UNDER THE NUT FOR ALL BOLTED ASSEMBLIES.

GENERAL NOTES (CONTINUED)

5. TIMBER BOARDWALK STRUCTURAL FASTENERS
- ALL LAG SCREWS, BOLTS, NUTS, AND WASHERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM F2329, UNLESS OTHERWISE NOTED.
 - ALL CONNECTING PLATES, BRACKETS, JOIST HANGERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A123, UNLESS OTHERWISE NOTED.
 - ALL STRUCTURAL BOLTS SHALL BE ASTM F3125 GRADE A325, UNLESS OTHERWISE NOTED.
 - A325 BOLTS SHALL COMPLY WITH "SPECIFICATIONS FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS", INCLUDING COMMENTARY.
 - ALL NUTS SHALL BE ASTM A563 GRADE A, UNLESS OTHERWISE NOTED.
 - ALL WASHERS SHALL BE ASTM F436 TYPE 1, UNLESS OTHERWISE NOTED. PROVIDE WASHERS UNDER BOTH THE BOLT HEAD AND NUT FOR ALL BOLTED ASSEMBLIES.
6. LUMBER
- LUMBER SIZES SHOWN ARE NOMINAL SIZES UNLESS OTHERWISE NOTED. LUMBER SHALL BE FURNISHED IN SIZES MEETING THE REQUIREMENTS OF THE NATIONAL DESIGN SPECIFICATIONS (NDS) FOR WOOD CONSTRUCTION, 2018 EDITION.
 - ALL LUMBER SHALL BE TREATED IN ACCORDANCE WITH THE AWPA (AMERICAN WOOD PRESERVERS ASSOCIATION) USE CATEGORY UC4C.
 - ALL LUMBER SHALL MEET THE REQUIREMENTS OF FDOT STANDARD SPECIFICATIONS SECTION 952, SOUTHERN PINE, GRADE NO. 1, AND BE PRESSURE TREATED IN ACCORDANCE WITH FDOT STANDARD SPECIFICATIONS SECTION 955 FOR BRACKISH WATER ENVIRONMENTS.
- H. CONCRETE SURFACE FINISH
- A CLASS 5 FINISH COATING SHALL BE APPLIED TO ALL EXPOSED CONCRETE SURFACES. SUBMIT COLOR AND TEXTURE FOR APPROVAL.
- I. PLAN DIMENSIONS
- ALL DIMENSIONS IN THESE PLANS ARE MEASURED IN FEET EITHER HORIZONTALLY OR VERTICALLY UNLESS OTHERWISE NOTED.
- J. UTILITIES
- FOR PLAN LOCATIONS OF EXISTING UTILITIES, SEE PLAN AND ELEVATION SHEET(S). LOCATIONS OF UTILITIES SHOWN IN THE PLANS ARE APPROXIMATE.
- K. JOINTS IN CONCRETE
- CONSTRUCTION JOINTS WILL BE PERMITTED ONLY AT THE LOCATIONS INDICATED IN THE PLANS. ADDITIONAL CONSTRUCTION JOINTS OR ALTERATIONS TO THOSE SHOWN SHALL REQUIRE APPROVAL OF THE ENGINEER.
- L. DECK SCREEDING
- SCREED THE RIDING SURFACE OF THE BRIDGE DECK TO ACHIEVE THE FINISH GRADE ELEVATIONS SHOWN IN THE PLANS. ACCOUNT FOR THEORETICAL DEFLECTIONS DUE TO DECK SELF WEIGHT, DECK CASTING SEQUENCE, DECK FORMING SYSTEMS, CONSTRUCTION LOADS, OVERLAYS AND TEMPORARY SHORING, ETC. AS REQUIRED.
- M. COORDINATION
- CONTRACTOR SHALL COORDINATE ALL CONSTRUCTION ACTIVITIES SUCH AS DELIVERIES, STORAGE, PARKING, AND WORK HOURS, WITH THE OWNER TO AVOID CONFLICTS WITH NORMAL PARK OPERATION.
- N. DEWATERING
- THE CONTRACTOR SHALL ANTICIPATE DEWATERING TO CONSTRUCT THE PIER FOUNDATIONS. THE CONTRACTOR IS TO INCLUDE THIS DEWATERING IN THE COST OF FOUNDATION CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING DEWATERING PERMITS AS REQUIRED BY THE SFWMD PRIOR TO COMMENCING DEWATERING ACTIVITIES.



REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				GENERAL NOTES (1 OF 2)		
		<div>PRELIMINARY NOT FOR CONSTRUCTION</div>					DESIGNED BY: JAH 09/23	ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.	
							CHECKED BY: TMW 09/23	-	LEE	EC2022- 41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	3	

PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:19 PM S:\brina
H:_Project\22\2213_EsteroRiverPedBridge\Structures\GeneralNotes.dgn

PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE

- A. EMPLOY THE SERVICES OF AN ELIGIBLE, QUALIFIED STEEL TRUSS BRIDGE FABRICATOR TO DESIGN, DETAIL, FABRICATE, AND DELIVER A STEEL TRUSS PEDESTRIAN BRIDGE MEETING THE DESIGN CRITERIA DESCRIBED ON THIS SHEET.
- B. THE STEEL TRUSS BRIDGE FABRICATOR SHALL BE ON THE FDOT LIST OF QUALIFIED METAL FABRICATION FACILITIES AND, AT A MINIMUM, MUST BE CERTIFIED IN THE AISC SIMPLE BRIDGE ACCREDITATION PROGRAM AS DESCRIBED IN TABLE 460-1 OF SECTION 460-1.2 OF THE FDOT SPECIFICATIONS IN ORDER TO BE CONSIDERED QUALIFIED TO PERFORM THE REQUIRED WORK. IN ORDER TO BE CONSIDERED ELIGIBLE FOR THIS PROJECT THE STEEL TRUSS BRIDGE FABRICATOR MUST BE SELECTED FROM LIST OF FABRICATORS ON SHEET 5.
- C. THE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE SHALL BE DESIGNED IN ACCORDANCE WITH THE FOLLOWING:
- BRIDGE PLANS
 - AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS 9TH EDITION (2020)
 - AASHTO GUIDE SPECIFICATIONS FOR THE DESIGN OF PEDESTRIAN BRIDGES (2009)
 - AISC STEEL CONSTRUCTION MANUAL, 15TH EDITION (2017)
 - FDOT DESIGN MANUAL (2023)
 - FDOT STRUCTURES MANUAL (2023)
 - FDOT STANDARD PLANS AND STANDARD SPECIFICATIONS (2023)
- D. DESIGN LOADINGS
- DEAD LOADS:
 - REINFORCED CONCRETE: 150 PCF
 - STRUCTURAL STEEL: 490 PCF
 - ALUMINUM ALLOY: 175 PCF
 - S.I.P. FORMS: 20 PSF
 - FUTURE WEARING SURFACE IS NOT INCLUDED.
 - LIVE LOADS:
 - PEDESTRIAN LIVE LOAD: 90 PSF
 - VEHICULAR LIVE LOAD: 4000 LB MAINTENANCE VEHICLE
 - PEDESTRIAN/BICYCLE RAILING LIVE LOAD: 50 PLF WITH 200 LB CONCENTRATED LOAD
 - WIND LOADS:
 - WIND LOADS SHALL BE COMPUTED IN ACCORDANCE WITH STRUCTURES DESIGN GUIDELINES SECTION 10.5 FOR PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGES.
 - LOADS FROM BOARDWALK (LOADS ARE APPLIED BELOW THE DECK LEVEL AT BEGIN AND END BRIDGE, SEE BOARDWALK CONNECTION DETAILS):
 - DEAD LOAD = 1.9 KIPS VERTICAL
 - LIVE LOAD = 6.5 KIPS VERTICAL
 - WIND LOAD: TRANSVERSE = ± 0.63 KIPS
LONGITUDINAL = ± 0.55 KIPS
- E. THE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE SHALL MEET OR EXCEED THE FOLLOWING PERFORMANCE REQUIREMENTS:
- THE BRIDGE SHALL BE DESIGNED FOR A 75-YEAR DESIGN LIFE.
 - THE FINAL CAMBER OF THE BRIDGE AFTER DEAD LOAD DEFLECTION SHALL FOLLOW THE PLAN PROFILE GRADE ON THE PLAN AND ELEVATION SHEETS.
 - THE MAXIMUM LIVE LOAD DEFLECTION SHALL BE LIMITED TO THE SPAN LENGTH DIVIDED BY 500.
 - THE MAXIMUM HORIZONTAL DEFLECTION DUE TO WIND LOADING SHALL BE THE SPAN LENGTH DIVIDED BY 500.
 - USE SLOTTED ANCHOR BOLT HOLES AT EACH SUPPORT TO ALLOW FOR THERMAL MOVEMENTS TO OCCUR IN BOTH DIRECTIONS.
- F. THE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE SHALL BE DESIGNED TO ACCOMMODATE THE SUBSTRUCTURE CONFIGURATION SHOWN IN THE PLANS (i.e. ABUTMENT SIZE, SHAPE, ELEVATION, ETC.). BRIDGE SEAT ELEVATIONS AND ANCHOR BOLT INSERT LOCATIONS MAY BE VARIED TO SUIT BRIDGE BEARINGS.
- G. TRUSS MATERIALS
- TRUSS MEMBERS (GALVANIZED AND PAINTED): SQUARE/RECTANGULAR HSS SECTIONS ASTM A847, GALVANIZED ASTM A123 WITH A MINIMUM WALL THICKNESS OF 1/4-INCHES.
 - PLATES & SHAPES: ASTM A588 OR A709 GRADE 50, GALVANIZED ASTM A123.
 - BOLTS: ASTM A325, TYPE 3 WITH ASTM A563 GRADE C3 NUTS AND ASTM F436, TYPE 3 WASHERS.
 - ANCHOR BOLTS: ASTM F1554 GRADE 105 WITH ASTM A563 GRADE A HEAVY HEX NUTS AND ASTM F436, TYPE 1 WASHERS. ANCHOR BOLTS, NUTS, AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM F2329.
 - WELD ELECTRODE: E70XX, REMOVE GALVANIZING OR PRIMER PRIOR TO WELDING.
- H. RAILING MATERIALS
- POSTS AND RAILS (NO COATING): ASTM B429 ALUMINUM WITH AN ALLOY AND TEMPER OF 6061-T6
 - SET SCREWS: ALUMINUM WITH AN ALLOY AND TEMPER OF 2024-T4 OR 7075-T73
 - WIRE ROPE (NO COATING): 1/4" \varnothing SS316, CLASS 1x19 STEEL STRAND
 - WELD ELECTRODE: ER40XX, CLEAN SURFACE PRIOR TO WELDING
- I. PAINTING OF NEW STRUCTURAL STEEL COMPONENTS:
PAINT ALL NEW STEEL COMPONENTS, UNLESS NOTED OTHERWISE, WITH AN INORGANIC ZINC COATING SYSTEM IN ACCORDANCE WITH FDOT SPECIFICATIONS SECTION 560 AND 975. ALL NEW STEEL COMPONENTS SHALL BE SHOP PRIMED AND INTERMEDIATE COATED IN ACCORDANCE WITH MANUFACTURER REQUIREMENTS. FINISH COAT ALONG WITH A CLEAR COAT SHALL BE APPLIED IN THE FIELD. FABRICATOR SHALL COORDINATE WITH THE VILLAGE OF ESTERO TO DETERMINE ACCEPTABLE PAINT COLORS.

PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE (CONTINUED)


- J. TOUCH-UP PAINT
BRIDGE SHALL BE PROVIDED WITH TOUCH-UP PAINT FOR AFTER ERECTION WHICH SHALL MATCH THE ACCEPTED COLOR. TOUCH-UP PAINTING INCLUDES ANY AND ALL PAINTING REQUIRED AFTER THE STRUCTURE REACHES THE SITE AND IS THE RESPONSIBILITY OF THE CONTRACTOR. THIS PAINTING SHALL INCLUDE, BUT NOT LIMITED TO, THE FOLLOWING AREAS:
- ANY AREAS DAMAGED DUE TO SHIPPING, HANDLING AND ERECTION OF THE BRIDGE.
 - BOLT HEADS AND EXPOSED AREAS OF BOLTS AND NUTS AS APPLICABLE.
 - UNGALVANIZED ANCHOR BOLTS IF NOT MADE OF CORROSION RESISTANT STEEL.
 - IF APPLICABLE, SMALL AREAS (2" EACH SIDE) AROUND BOLTED FIELD SPLICES, DESIGNED AS "SLIP CRITICAL" WHERE ONE OR ALL PAINT COATS MAY BE REQUIRED TO BE LEFT OFF THE FAYING SURFACES OF THESE CONNECTIONS.
 - ALL FIELD WELDS ARE REQUIRED TO BE PAINTED.
- K. CAP ALL OPEN-ENDED TUBING AND COMPLETELY SEAL AROUND WELDED JOINTS SUCH THAT NO CREVICE OR OPENING EXISTS WHERE WATER CAN COLLECT ON OR PENETRATE THE JOINT.
- L. FULLY DETAILED SHOP DRAWINGS AND CALCULATIONS SIGNED AND SEALED BY THE CONTRACTOR'S ENGINEER OF RECORD (CEOR) SHALL BE PROVIDED TO THE EOR FOR REVIEW AND APPROVAL PRIOR TO BEGINNING THE FABRICATIONS OF THE BRIDGE. THE CEOR MUST BE A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF FLORIDA AND SHALL BE AN EMPLOYEE OF THE QUALIFIED BRIDGE FABRICATOR OR SHALL BE AN EMPLOYEE OF AN ENGINEERING FIRM PREQUALIFIED IN THE FDOT WORK GROUP CATEGORY 4.2.2 MAJOR BRIDGE, STEEL.
- M. STEEL MEMBER TESTING:
- IDENTIFY ALL FRACTURE CRITICAL MEMBERS ON THE SHOP DRAWINGS.
 - ASTM A709 CHARPY V-NOTCH TESTING IS REQUIRED FOR ALL TENSION MEMBERS.
 - IMPACT TESTING SHALL BE PERFORMED AS FOLLOWS:
 - TEST NON-FRACTURE CRITICAL TENSION MEMBERS IN ACCORDANCE WITH ASTM A709.
 - PRIMARY TENSION CHORDS IN A TWO TRUSS BRIDGE MAY BE CONSIDERED NON-FRACTURE CRITICAL DUE TO FRAME ACTION.
 - TEST FRACTURE CRITICAL MEMBERS IN ACCORDANCE WITH ASTM A709.
- N. FABRICATION OF THE STEEL TRUSS PEDESTRIAN BRIDGE STRUCTURE SHALL BE PERFORMED IN ACCORDANCE WITH FDOT SPECIFICATIONS SECTION 460.
- O. THE MINIMUM THICKNESS OF BRIDGE DECK SHALL BE 6-INCHES WITH NO ALLOWANCE FOR ONE-HALF INCH SACRIFICIAL THICKNESS. STAY-IN-PLACE (S.I.P.) FORMS SHALL BE UTILIZED FOR THE DECK CONSTRUCTION. PROVIDE GALVANIZED OR VINYL COATED FORMS. SUBMIT THE PRODUCT TO THE EOR FOR APPROVAL.
- P. PEDESTRIAN/BICYCLE RAILING ON BRIDGE:
- STEEL TRUSS BRIDGE FABRICATOR SHALL SUBMIT SHOP DRAWING OF PROPOSED RAILING SYSTEM IN ACCORDANCE WITH THE PLAN PROVISIONS TO THE EOR FOR APPROVAL. SHOP DRAWINGS SHALL INCLUDE THE RAIL ANCHOR DESIGN, ALL WELD AND FASTENER DETAILS, AND THE STRAND TENSIONING PLAN AND DETAILS.
 - STEEL TRUSS BRIDGE FABRICATOR MAY ELECT TO SUBMIT SHOP DRAWINGS OF AN ALTERNATE RAILING SYSTEM WHICH MUST BE APPROVED BY BOTH THE EOR AND THE VILLAGE OF ESTERO. ANY ALTERNATE MUST MEET THE MINIMUM CRITERIA LISTED BELOW.
 - DESIGN MUST BE IN ACCORDANCE WITH STATED DESIGN LOADING, AASHTO LRFD, FDOT STRUCTURES DESIGN MANUAL, AND THE AMERICANS WITH DISABILITIES ACT (ADA) STANDARDS SECTION 505.
 - RAILING SYSTEM MUST INCLUDE AN UNPAINTED CIRCULAR ALUMINUM TOP RAIL OR HANDRAIL.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				GENERAL NOTES (2 OF 2)		
		<div>PRELIMINARY NOT FOR CONSTRUCTION</div>					DESIGNED BY: JAH 09/23	ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.	
							CHECKED BY: TMW 09/23	-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	4	


PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


12/27/2023 12:26:20 PM S:\projects\2213_EsteroRiverPedBridge\Structures\TrussConfiguration.dgn




TRUSS 1




TRUSS 2



TRUSS 3



TRUSS 4




TRUSS 5

TRUSS CONFIGURATIONS

ALLOWABLE TRUSS CONFIGURATIONS					
	TRUSS 1	TRUSS 2	TRUSS 3	TRUSS 4	TRUSS 5
PERMITTED (Y/N)	Y	N	N	Y	N



SHAPE 1
(STRUCTURAL TUBE)




SHAPE 2
(STRUCTURAL PIPE)


TRUSS MEMBER SHAPES

ALLOWABLE TRUSS MEMBER SHAPES		
	SHAPE 1	SHAPE 2
PERMITTED (Y/N)	Y	N

LIST OF APPROVED FABRICATORS:
1. CONTECH BRIDGE SOLUTIONS
2. G&G STEEL, INC.
3. FLORIDA STRUCTURAL STEEL AND CONSTRUCTION, INC.



SECTION 1
(THROUGH TRUSS)



SECTION 2
(BOX TRUSS)

BRIDGE CROSS-SECTIONS

ALLOWABLE BRIDGE * CROSS-SECTIONS		
	SHAPE 1	SHAPE 2
PERMITTED (Y/N)	Y	N

* THROUGH TRUSS BRIDGES ARE ACCEPTABLE ONLY FOR SPANS LESS THAN OR EQUAL TO 150'. FOR SPANS OVER 150' BOX TRUSS BRIDGES ARE REQUIRED.

NOTES:
1. ELIGIBLE PEDESTRIAN BRIDGE PRODUCERS:
INCLUDED IN THIS PLAN SET ARE PEDESTRIAN BRIDGE DATA SHEETS SUBMITTED BY BRIDGE PRODUCERS ELIGIBLE TO PARTICIPATE IN THIS PROJECT. PRODUCERS WHO FAILED TO SUBMIT A DATA SHEET ARE EXCLUDED FROM PARTICIPATION. NO COST SAVINGS INITIATIVE PROPOSAL SHALL BE ACCEPTED FOR THE TRUSS SUPERSTRUCTURE PORTION OF THE PROJECT. CONTACT INFORMATION FOR THE ELIGIBLE PRODUCERS IS INCLUDED IN THE DATA SHEETS.
2. ALLOWABLE SUPERSTRUCTURE OPTIONS:
ALL ALLOWABLE SUPERSTRUCTURE OPTIONS ARE INDICATED BY A "Y" IN THE TABLES ON THIS SHEET. FOR MULTI-SPAN BRIDGES USE THE SAME TRUSS BRIDGE OPTIONS AND DEPTH OF TRUSS FOR EACH SPAN.

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
		PRELIMINARY NOT FOR CONSTRUCTION			

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901



DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO		
ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:	REF. DWG. NO.
TRUSS CONFIGURATION	
PROJECT NAME:	SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE	5

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


12/27/2023 12:26:21 PM S:\projects\12213_EsteroRiverPedBridge\Structures\ProjectLocation.dgn



REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:		
									LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		
PRELIMINARY NOT FOR CONSTRUCTION													6

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:28 PM S:\Projects\22213_EsteroRiverPedBridge\Structures\SlopeProtectionDetails of 2.dgn



PLAN

- NOTES:
1. RIPRAP RUBBLE AROUND END WALLS, TIMBER PILES, AND PIERS SHOULD BE PLACED BEFORE THE PEDESTRIAN BRIDGE AND TIMBER BOARDWALK SUPERSTRUCTURE IS INSTALLED. INSTALL TIMBER PILES BEFORE RIPRAP AROUND THE END WALLS.
 2. RIPRAP RUBBLE MATERIALS, CONSTRUCTION, AND INSTALLATION PER FDOT STANDARD SPECIFICATIONS SECTION 530.
 3. FILTER FABRIC SHALL BE TYPE D-2, IN ACCORDANCE WITH SPECIFICATIONS SECTION 985. SPLICE LENGTH SHALL BE IN ACCORDANCE WITH SPECIFICATIONS SECTION 514.

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					


THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23


VILLAGE OF ESTERO		
ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:		REF. DWG. NO.
SLOPE PROTECTION DETAILS (1 OF 2)		
PROJECT NAME:		SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE		7

12/27/2023 12:26:30 PM S:\projects\2213_EsteroRiverPedBridge\Structures\SlopeProtectionDetails\2 of 2.dgn





SECTION A-A - BANK AND SHORE DETAIL
FOR END WALLS 1 & 2 PROTECTION



SECTION B-B - BANK AND SHORE DETAIL
FOR PIERS 1 & 2 PROTECTION

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY:	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		JAH 09/23				SLOPE PROTECTION DETAILS (2 OF 2)		
		<div>PRELIMINARY NOT FOR CONSTRUCTION</div>					CHECKED BY:	ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.	
			TMW 09/23										
						DESIGNED BY:							
						JAH 09/23	-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	8		
						CHECKED BY:							
						TMW 09/23							


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 65460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:	PLAN & ELEVATION (1 OF 2)	REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				ROAD NO.		COUNTY
							DESIGNED BY: JAH 09/23	-	LEE	EC2022 - 41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	9	
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>							CHECKED BY: TMW 09/23						

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 81G15-23.004, F.A.C.

12/27/2023 12:26:37 PM S:\projects\2213_EsteroRiverPedBridge\Structures\PlanAndElevation2of2.dgn




NOTES:
1. THE MANUFACTURED CAMBER OF THE STEEL TRUSS AT MIDSPAN SHALL BE $1'-0\frac{5}{8}" + \Delta$, WHERE Δ IS THE FINAL DEAD LOAD DEFLECTION OF THE BRIDGE INCLUDING ALL STEEL AND CONCRETE DECK COMPONENTS. SEE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE GENERAL NOTES FOR MORE INFORMATION.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION						PLAN & ELEVATION (2 OF 2)		
								ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.	
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>								-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	10	

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:37 PM S:\projects\2213_EsteroRiverPedBridge\Structures\TypicalSection.dgn




TYPICAL SECTION

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY:	VILLAGE OF ESTERO			SHEET TITLE:	REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		JAH 09/23				TYPICAL SECTION	
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>							CHECKED BY:					
							TMW 09/23	ROAD NO.	COUNTY	CONTRACT NO.		
							DESIGNED BY:				SHEET NO.	
						JAH 09/23	-	LEE	EC2022-41	11		
						CHECKED BY:						
						TMW 09/23 <td></td> <td></td> <td></td> <td></td> <td></td>						


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:26:38 PM S:\projects\22213_EsteroRiverPedBridge\Structures\SuperstructureDetails.dgn



RAILING SECTION


RAILING ELEVATION
(STEEL TRUSS AND TIMBER BOARDWALK OMITTED FOR CLARITY)




RAIL JOINT DETAIL (TOP SHOWN, BOTTOM SIMILAR)

NOTES:


1. TOP AND BOTTOM RAILS SHALL BE 3" Ø ALUMINUM PIPE WITH A 3/16" WALL THICKNESS.
2. RAIL POSTS SHALL BE 2"x2"x1/4" SQUARE ALUMINUM TUBING. SPACING BETWEEN RAIL POSTS SHALL NOT EXCEED 5 FEET. THROUGH-DRILL RAIL POSTS TO ACCOMMODATE STEEL STRANDS. PROVIDE DRAIN HOLES AT BOTTOM OF EACH RAIL POST.
3. WIRE ROPE SHALL BE 1/4" Ø SS316, CLASS 1x19 STEEL STRAND. STRAND SECTIONS SHALL BE TENSIONED AND ANCHORED AT RAIL JOINTS TO REMOVE SLACK. MAX TENSIONING PER STAND IS 200LB. ALL STEEL STRANDS SHALL BE ISOLATED FROM ALUMINUM RAILING BY RUBBER OR PLASTIC GROMMETS AND WASHERS TO PREVENT GALVANIC CORROSION.
4. RAIL JOINTS SHALL BE INCLUDED WITH A MINIMUM SPACING OF 10 FEET AND A MAXIMUM SPACING OF 24 FEET. SET SCREWS FOR RAIL JOINTS SHALL BE 1/4"x3/4" PAN HEAD ALUMINUM SCREWS AND MUST BE SET FLUSH AGAINST THE OUTSIDE FACE OF RAILS. DO NOT PROVIDE SET SCREWS FOR RAILS AT FREE END OF RAIL JOINTS. JOINT SLEEVE SHALL BE 2.5" Ø ALUMINUM PIPE WITH A 1/8" WALL THICKNESS.
5. TOP AND BOTTOM RAIL ANCHORS SHALL BE DESIGNED BY THE STEEL TRUSS BRIDGE FABRICATOR. RAIL ANCHORS SHALL BE SPACED AT A MAXIMUM OF 12 FEET WITH TOP AND BOTTOM ANCHORS PRESENT WITHIN 3 FEET OF THE RAILING ENDS. RAIL ANCHORS SHALL BE DESIGNED IN ACCORDANCE WITH THE AMERICANS WITH DISABILITIES ACT (ADA) STANDARDS SECTION 505. INCLUDE RUBBER OR PLASTIC COMPONENTS AS NEEDED TO ISOLATE ALUMINUM RAILING AND RAILING CONNECTION FROM STEEL TRUSS TO PREVENT GALVANIC CORROSION.
6. ALL BURS AND SHARP EDGES ON THE RAIL SYSTEM SHALL BE GROUND AFTER INSTALLATION.
7. SEE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE NOTE P FOR ADDITIONAL PEDESTRIAN/BICYCLE RAILING NOTES.



TYPICAL SLAB REINFORCEMENT DETAIL



SECTION - CONTROL JOINT
(AT EVERY FLOOR BEAM)



CONSTRUCTION JOINT DETAIL
(AS REQUIRED)

DECK NOTES:

1. GALVANIZED FORM DECK SHALL BE METAL DECK GROUP (CFD2) 2" x 36" x 30'-0" 18 GAGE G-165 COMPOSITE DECKING. THE STEEL TRUSS BRIDGE FABRICATOR SHALL DETAIL THE FORM DECK LAYOUT AND ATTACHMENT TO THE FLOOR BEAMS.
2. CONCRETE COVER OF 2 1/2" ABOVE LONGITUDINAL REINFORCEMENT SHALL BE MAINTAINED.
3. THE CONCRETE DECK IS DESIGNED FOR 12'-0" MAXIMUM FLOOR BEAM SPACING. IF THE FLOOR BEAM SPACING PROVIDED BY THE STEEL TRUSS BRIDGE FABRICATOR IS GREATER THAN 12'-0", PROVIDE AN ALTERNATE DESIGN TO ACCOMMODATE THE PROPOSED SPACING.

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

PRELIMINARY
NOT FOR CONSTRUCTION

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO

ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:

SUPERSTRUCTURE DETAILS

REF. DWG. NO.

PROJECT NAME:



ESTERO ON THE RIVER PEDESTRIAN BRIDGE

SHEET NO.

12

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:27:21 PM S:\projects\22213_EsteroRiverPedBridge\Structures\BridgeHydraulic.dgn




REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO		
ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:		REF. DWG. NO.
BRIDGE HYDRAULIC RECOMMENDATIONS		
PROJECT NAME:		SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE		13



(REFERENCE)	EXISTING STRUCTURES				PROPOSED STRUCTURE CONCRETE PILES
	(1)	(2)	(3)	(4)	
FOUNDATION	N/A	N/A	N/A	N/A	134'-2"
OVERALL LENGTH	N/A	N/A	N/A	N/A	134'-2"
SPAN LENGTH	N/A	N/A	N/A	N/A	PREFAB. TRUSS
TYPE CONSTRUCTION	N/A	N/A	N/A	N/A	-
AREA OF OPENING@D.F.	N/A	N/A	N/A	N/A	12'-0"
BRIDGE WIDTH	N/A	N/A	N/A	N/A	12.76
ELEV. LOW MEMBER	N/A	N/A	N/A	N/A	

HYDRAULIC DESIGN DATA

NOTE:
This hydraulic data is a summary of design calculations and is provided for informational purposes only. The user is cautioned against the assumption of precision for the discharge rates, units are in cubic feet per second and the design stages, feet-NAVD 1988.

TERMS:
Design Flood: Utilized to assure a desired level of hydraulic performance.
Base Flood: Has a 1% chance of being exceeded in any given year (100 year frequency)
Overtopping Flood: Causes flow over the highway, over a watershed divide, or thru emergency relief structures.
Greatest Flood: The most severe that can be predicted where overtopping is not practicable.

WATER SURFACE ELEVATIONS:		N.H.W. (Non-Tidal)	N/A	M.H.W. (Tidal)	7.80
		CONTROL (Non-Tidal)	N/A	M.L.W. (Tidal)	3.80
FLOOD DATA:		MAX. EVENT OF RECORD	DESIGN FLOOD	BASE FLOOD	
STAGE ELEV. NAVD (ft)		13.30	11.80	11.80	
DISCHARGE (cfs)		-	5,331	5,331	
AVERAGE VELOCITY (f/s)		-	1.37	1.37	
EXCEEDANCE PROB. (%)		-	1	1	
FREQUENCY (yr.)		-	100	100	

SCOUR PREDICTIONS FOR PROPOSED STRUCTURE DESCRIBED ABOVE:		TOTAL SCOUR ELEVATION	
PIER INFORMATION		LONG TERM	WORST CASE < 100 yr.
SIZE AND TYPE		SCOUR ELEV. FREQ. (yr.)	SCOUR ELEV. FREQ. (yr.)
14" SQ. PILES		100	500
12" TIMBER PILES		CONCRETE PILES WILL BE ARMORED WITH RIP-RAP RUBBLE, BANK AND SHORE	
GRAVITY WALL ABUTMENTS		TIMBER PILES WILL BE ARMORED WITH BEDDING STONE	
		ABUTMENTS WILL BE ARMORED WITH RIP-RAP, RUBBLE, BANK AND SHORE	


HYDRAULIC RECOMMENDATIONS													
1. BEGIN BRIDGE STATION		10+94.42		END BRIDGE STATION		12+28.59		SKEW ANGLE		0°			
2. CLEARANCE PROVIDED:		NAV: HORIZ. N/A		VERT. N/A		ABOVE EL. N/A		DRIFT: HORIZ. N/A		VERT. N/A		ABOVE EL. N/A	
3. MINIMUM CLEARANCE:		NAV: HORIZ. N/A		VERT. N/A		ABOVE EL. N/A		DRIFT: HORIZ. N/A		VERT. N/A		ABOVE EL. N/A	
4. ABUTMENTS:													
BEGIN BRIDGE						END BRIDGE							
RUBBLE GRADE:						BEGIN RIP-RAP, RUBBLE						END RIP-RAP, RUBBLE	
SLOPE:						MATCH EXISTING GRADE						MATCH EXISTING GRADE	
BURIED OR NON-BURIED HORIZ. TOE:						BURIED TOE						BURIED TOE	
TOE HORIZ. DISTANCE:						BURIED TOE, N/A						BURIED TOE, N/A	
LIMIT OF PROTECTION:													
5. DECK DRAINAGE: THE PEDESTRIAN BRIDGE IS OPEN DECK AND DRAINS TOWARD THE RIVER AND SITE													

REMARKS: FEMA NO RISE CERTIFICATION AND HYDRAULIC MODELING PROVIDED BY JR EVANS ENGINEERING, INC.



NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:27:22 PM S:\Project22\2213_EsteroRiverPedBridge\Structures\ReportOfCoreBorings.dgn

Bore # B-1
Latitude 26.43446
Longitude -81.80869
Elevation 9.2'
Vertical Datum NAVD88
Date 9/11/2023
Driller Dancor
Hammer Auto
Rig CME 55




Bore # B-2
Latitude 26.43492
Longitude -81.80847
Elevation 8.7'
Vertical Datum NAVD88
Date 9/12/2023
Driller Dancor
Hammer Auto
Rig CME 55



BORING LOCATION

LEGEND



APPROXIMATE SPT BORING LOCATION
N STANDARD PENETRATION RESISTANCE IN BLOWS PER FOOT
WATER LEVEL MEASURED ON DATE BORING INITIATED
NAVD88 NORTH AMERICAN VERTICAL DATUM OF 1988
w MOISTURE CONTENT
-200 PERCENT PASSING THE NO. 200 STANDARD SIEVE

GRANULAR MATERIALS		
RELATIVE DENSITY	SAFETY HAMMER SPT N-VALUE (BLOW/FOOT)	AUTOMATIC HAMMER SPT N-VALUE (BLOW/FOOT)
VERY LOOSE	LESS THAN 4	LESS THAN 3
LOOSE	4 - 10	3 - 8
MEDIUM DENSE	10 - 30	8 - 24
DENSE	30 - 50	24 - 40
VERY DENSE	GREATER THAN 50	GREATER THAN 40

SILTS AND CLAYS		
CONSISTENCY	SAFETY HAMMER SPT N-VALUE (BLOW/FOOT)	AUTOMATIC HAMMER SPT N-VALUE (BLOW/FOOT)
VERY SOFT	LESS THAN 2	LESS THAN 1
SOFT	2 - 4	1 - 3
FIRM	4 - 8	3 - 6
STIFF	8 - 15	6 - 12
VERY STIFF	15 - 30	12 - 24
HARD	GREATER THAN 30	GREATER THAN 24

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					

CHRISTOPHER GALLAGHER, P.E.
P.E. LICENSE NUMBER 96198
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
SDS 06/23
CHECKED BY:
CRG 06/23
DESIGNED BY:
SDS 06/23
CHECKED BY:
CRG 06/23



VILLAGE OF ESTERO

ROAD NO. COUNTY CONTRACT NO.
- LEE EC2022-41

SHEET TITLE:		REF. DWG. NO.
REPORT OF CORE BORINGS		
PROJECT NAME:		SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE		14

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:27:24 PM S:\projects\122723_EsteroRiverPedBridge\Structures\Foundation\layout.dgn



- LEGEND**
- PROPOSED 14" SQUARE PRESTRESSED CONCRETE PILES
 - PROPOSED 14" SQUARE PRESTRESSED CONCRETE TEST PILES
 - PROPOSED 12" DIA. TIMBER PILES
 - ◆ APPROXIMATE BORING LOCATION FOR BORING DATA, SEE REPORT OF CORE BORINGS SHEET

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION						FOUNDATION LAYOUT		
								ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:		SHEET NO.
								-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		15

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:27:24 PM S:\projects\2213_EsteroRiverPedBridge\Structures\PileDataTable.dgn

PILE DATA TABLE																					Table Date 01/01/16	
INSTALLATION CRITERIA									DESIGN CRITERIA								PILE CUT-OFF ELEVATIONS					
PIER or BENT NUMBER	PILE SIZE (in.)	NOMINAL BEARING RESISTANCE (tons)	NOMINAL UPLIFT RESISTANCE (tons)	MINIMUM TIP ELEVATION (ft.)	TEST PILE LENGTH (ft.)	ORDER PILE LENGTH (ft.)	REQUIRED JET ELEVATION (ft.)	REQUIRED PREFORM ELEVATION (ft.)	FACTORED DESIGN LOAD (tons)	FACTORED DESIGN UPLIFT LOAD (tons)	DOWN DRAG (tons)	TOTAL SCOUR RESISTANCE (tons)	NET SCOUR RESISTANCE (tons)	100-YEAR SCOUR ELEVATION (ft.)	Ø COMPRESSION	Ø UPLIFT	PILE 1	PILE 2	PILE 3	PILE 4		
PIER 1	14 *	69	N/A	-19	60	N/A	N/A	N/A	45	N/A	N/A	N/A	N/A	N/A	0.65	N/A	6.3	6.3	6.3	6.3		
PIER 2	14 *	71	N/A	-24	60	N/A	N/A	N/A	46	N/A	N/A	N/A	N/A	N/A	0.65	N/A	2.2	2.2	2.2	2.2		
TIMBER BOARDWALK	12 **	8	N/A	10 ***	N/A	30	N/A	N/A	5	N/A	N/A	N/A	N/A	N/A	0.65	N/A	SEE NOTE 4					

* 14" SQUARE PRESTRESSED CONCRETE PILES
** 12" DIA. TIMBER PILES
*** MINIMUM TIP ELEVATION REPORTED AS LENGTH OF PENETRATION BELOW EXISTING GRADE

$$\frac{\text{Factored Design Load} + \text{Net Scour Resistance} + \text{Down Drag}}{\varnothing} \leq \text{Nominal Bearing Resistance}$$

UPLIFT RESISTANCE - The ultimate side friction capacity that must be obtained below the 100 year scour elevation to resist pullout of the pile (Specify only when design requires uplift capacity).
TOTAL SCOUR RESISTANCE - An estimate of the ultimate static side friction resistance provided by the scourable soil.
NET SCOUR RESISTANCE - An estimate of the ultimate static side friction resistance provided by the soil from the required preformed or jetting elevation to the scour elevation.
100-YEAR SCOUR ELEVATION - Estimated elevation of scour due to the 100 year storm event.





PILE INSTALLATION NOTES:

1. CONTRACTOR TO VERIFY LOCATIONS OF ALL UTILITIES PRIOR TO ANY PILE INSTALLATION ACTIVITIES.
2. MINIMUM TIP ELEVATION IS REQUIRED FOR LATERAL STABILITY AT ALL LOCATIONS AND SHALL MEET THE REQUIREMENTS OF FDOT SPECIFICATIONS SECTION 455.
3. NO JETTING WILL BE ALLOWED WITHOUT APPROVAL OF THE ENGINEER.
4. THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF TIMBER PILE CUT-OFF ELEVATIONS AND SELECTED PILE DRIVING HAMMER TO EOR FOR APPROVAL PRIOR TO DRIVING PILES.
5. DURING INSTALLATION OF FOUNDATIONS, PROTECT AND MONITOR EXISTING STRUCTURES IN ACCORDANCE WITH FDOT SPECIFICATIONS SECTION 455-1.1.
6. ALL TEST PILES SHALL BE DYNAMICALLY MONITORED IN ACCORDANCE WITH FDOT SPECIFICATIONS SECTION 455.
7. TEST PILES SHALL BE DRIVEN IN POSITION OF A PERMANENT PLUMB PILE AT LOCATIONS SHOWN ON THE FOUNDATION LAYOUT SHEET OR AS DIRECTED BY THE ENGINEER.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				PILE DATA TABLE		
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>							DESIGNED BY: JAH 09/23	ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:	SHEET NO.	
							CHECKED BY: TMW 09/23	-	LEE	EC2022- 41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	16	





PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- NOTES:
1. WORK THIS SHEET WITH FOUNDATION LAYOUT AND FOOTING DETAILS SHEET FOR DIMENSION, DETAILS, AND PILE LAYOUTS.
 2. DIMENSIONS AND ELEVATIONS ARE TAKEN ALONG THE PIER CENTERLINE, UNLESS NOTED OTHERWISE.


REVISIONS					<div>THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901</div>	<div>DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23</div>	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY						DESCRIPTION	PIER 1 PLAN & ELEVATION	
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>							ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:		SHEET NO.
							-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		17



NOTES:

1. WORK THIS SHEET WITH FOUNDATION LAYOUT AND FOOTING DETAILS SHEET FOR DIMENSION, DETAILS, AND PILE LAYOUTS.
2. DIMENSIONS AND ELEVATIONS ARE TAKEN ALONG THE PIER CENTERLINE, UNLESS NOTED OTHERWISE.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				ROAD NO.	COUNTY	
							DESIGNED BY: JAH 09/23	-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		18
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>							CHECKED BY: TMW 08/23						




SECTION B-B

PRELIMINARY
NOT FOR CONSTRUCTION


REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23	VILLAGE OF ESTERO			SHEET TITLE:	PIER DETAILS (1 OF 3)	REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		CHECKED BY: TMW 09/23				ROAD NO.		COUNTY
							DESIGNED BY: JAH 09/23	-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE	19	
							CHECKED BY: TMW 09/23						
<div>PRELIMINARY NOT FOR CONSTRUCTION</div>													

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


12/27/2023 12:27:28 PM S:\projects\12213_EsteroRiverPedBridge\Structures\PierDetails\2of3.dgn




SECTION A-A




SECTION C-C




SECTION D-D



SECTION E-E



SECTION F-F



BRIDGE SEAT DETAILS
(PIER REINFORCEMENT NOT SHOWN FOR CLARITY)

NOTES:


1. ADJUST TOP OF BRIDGE SEAT ELEVATIONS TO ACCOMMODATE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE BEARING CONFIGURATION. SUBMIT FINAL TOP OF BRIDGE SEAT ELEVATIONS WITH SIGN AND SEALED PREFABRICATED STEEL TRUSS SHOP DRAWINGS AND CALCULATIONS FOR REVIEW AND APPROVAL.
2. IN THE VICINITY OF THE CONSTRUCTION JOINT, FIELD BEND REINFORCEMENT AS NECESSARY TO MAINTAIN MINIMUM REINFORCEMENT COVER.
3. NUMBERS AND LOCATIONS OF ANCHOR BOLTS SHALL BE DETERMINED BY THE STEEL TRUSS BRIDGE FABRICATOR. SUBMIT NUMBERS AND LOCATIONS OF ANCHOR BOLTS WITH SIGNED AND SEALED PREFABRICATED STEEL TRUSS SHOP DRAWINGS AND CALCULATIONS FOR REVIEW AND APPROVAL.
4. BEARING PAD, BEARING PLATE, AND ANCHOR BOLTS ARE TO BE DESIGNED AND DETAILED BY BRIDGE FABRICATOR. MEMBERS SHALL BE SIZED TO ACCOMMODATE SUBSTRUCTURE CONFIGURATION.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE: PIER DETAILS (2 OF 3)		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:		SHEET NO.
								-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		20


PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


12/27/2023 12:27:28 PM S:\projects\12213_EsteroRiverPedBridge\Structures\PierDetail\3043.dgn



BEGIN BRIDGE ELEVATION VIEW



SECTION A-A



BOARDWALK CONNECTION DETAIL
AT BEGIN AND END BRIDGE

- NOTES:
1. THE BRIDGE FABRICATOR SHALL ACCOMMODATE A BOARDWALK CONNECTION AT THE BEGIN AND END OF THE BRIDGE. THE BRIDGE FABRICATOR MAY PROVIDE AN ALTERNATE DESIGN AND DETAILS FOR THE BOARDWALK CONNECTION TO THE STEEL TRUSS. SEE PREFABRICATED STEEL TRUSS PEDESTRIAN BRIDGE GENERAL NOTES FOR BOARDWALK LOADS ON ANGLE BRACKET. SUBMIT CONNECTION DESIGN WITH SIGNED AND SEALED PREFABRICATED STEEL TRUSS SHOP DRAWINGS AND CALCULATIONS FOR REVIEW AND APPROVAL.

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO

ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:

PIER DETAILS (3 OF 3)

REF. DWG. NO.


PROJECT NAME:

ESTERO ON THE RIVER PEDESTRIAN BRIDGE


SHEET NO.

21


12/27/2023 12:27:29 PM S:\projects\2213_EsteroRiverPedBridge\Structures\FootingDetails.dgn



PLAN



SIDE ELEVATION



ELEVATION

- NOTES:
1. ROTATE 6F01 BARS AS NECESSARY TO MAINTAIN REQUIRED COVER FROM THE CONCRETE EDGE AND PILE FACE.

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE: FOOTING DETAILS ESTERO ON THE RIVER PEDESTRIAN BRIDGE	REF. DWG. NO. SHEET NO. 22
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	CONTRACT NO.		
								-	LEE	EC2022-41		

PRELIMINARY
NOT FOR CONSTRUCTION

12/27/2023 12:27:30 PM S:\projects\12213_EsteroRiverPedBridge\Structures\ReinforcingBarList.dgn

Mark		Length		No	TYP	STY		B		C		D		E		F		H		J		K		N	f
Size	Des	Ft	In	Bars	BAR	A	G	Ft	In	Ft	In	Ft	In	Ft	In	Ft	In	Ft	In	Ft	In	Ft	In	NO	ANG
PIER 1 AND 2 FOOTING																									
No. Required = 2																									
6	F01	4' - 6"		32	17	3		3' - 6"																	
6	F02	4' - 6"		6	18	3	3	2' - 6"																	
6	F03	13' - 2"		4	18	3	3	11' - 2"																	
6	F04	8' - 6"		20	18	3	3	6' - 6"																	
6	F05	18' - 2"		8	18	3	3	16' - 2"																	
6	F06	8' - 6"		21	18	3	3	6' - 6"																	
6	F07	18' - 2"		9	18	3	3	16' - 2"																	
6	F08	8' - 6"		2	18	3	3	6' - 6"																	
6	F09	18' - 2"		2	18	3	3	16' - 2"																	
6	F10	3' - 5"		60	18	3	3	1' - 5"																	
PIER 1 AND 2 CAP																									
No. Required = 2																									
6	C01	16' - 2"		14	1			16' - 2"																	
4	C02	6' - 7"		17	4	5	5	1' - 5"		1' - 6"															
4	C03	4' - 4"		6	1			4' - 4"																	
4	C04	1' - 6"		16	1			1' - 6"																	
4	C05	4' - 4"		10	11			1' - 2"		2' - 0"		1' - 2"													
4	C06	3' - 9"		12	11			1' - 2"		1' - 5"		1' - 2"													
PIER 1 COLUMN																									
No. Required = 2																									
6	P01	4' - 10"		16	17	3		3' - 10"																	
4	P02	6' - 9"		5	4	5	5	2' - 0"		1' - 0"															
PIER 2 COLUMN																									
No. Required = 2																									
6	P01	9' - 0"		16	17	3		8' - 0"																	
4	P02	6' - 9"		13	4	5	5	2' - 0"		1' - 0"															
Note:																									

REVISIONS					
DATE	BY	DESCRIPTION		DATE	BY
		<div>PRELIMINARY NOT FOR CONSTRUCTION</div>			



THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO		
ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:	REF. DWG. NO.
REINFORCING BAR LIST	
PROJECT NAME:	SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE	23

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




* SEE FOUNDATION LAYOUT SHEET

NOTES:


1. ATTACH ALL RAILING BOARDS TO RAILING POST WITH GRIP-RITE #9x3" WOOD CONSTRUCTION SCREW W/ PREDRILLING TIP, PRIMEGUARD PLUS COATING SPACED AT 6" O.C.
2. ATTACH WIRE MESH TO RAILING BOARDS WITH GRIP-RITE #8x1¼" WOOD CONSTRUCTION SCREW W/ PREDRILLING TIP, PRIMEGUARD PLUS COATING SPACED AT 6" O.C.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
84


12/27/2023 12:27:32 PM S:\projects\2213_EsteroRiverPedBridge\Structures\Boardwalk\FramingPlan.dgn




BOARDWALK FRAMING PLAN



RIM JOIST TO RAILING POST CONNECTION
AT INTERMEDIATE SUPPORTS



BOARDWALK CONNECTION DETAIL
AT BEGIN AND END BRIDGE



PROVIDE 3/16" x 1 1/4" LONG SLOTTED HOLE AT BASE CONNECTION TO L7x4x3/8 BRACKET

PROVIDE 3/16" STANDARD HOLE AT CONNECTION TO 2"x10" JOIST

JOIST BRACKET DETAIL

MATERIALS LIST	
PILES	12" DIA SYP ASTM D25, 2.5 CCA
HEADERS	2" x 12" x 12' SYP GRADE NO. 1, S4S 0.60 CCA
JOIST	2" x 10" x 12' SYP GRADE NO. 1, S4S 0.60 CCA
BLOCKING	2" x 10" SYP GRADE NO. 1, S4S 0.60 CCA
DECKING	2" x 6" x 12' SYP GRADE NO. 1, S4S 0.60 CCA
RAIL POST	4" x 6" SYP GRADE NO. 1, S4S 0.60 CCA
HAND RAIL	2" x 8" SYP GRADE NO. 1, S4S 0.60 CCA
TOP RAIL BOARDS	2" x 6" SYP GRADE NO. 1, S4S 0.60 CCA
BOTTOM RAIL BOARDS	2" x 4" SYP GRADE NO. 1, S4S 0.60 CCA
RAILING MESH	WWF GAUGE 10.5, 1.5" x 1.5" W/ BLACK PVC COATING

CONNECTOR AND FASTENER SCHEDULE		
CONNECTION LOCATION	TYPE	NUMBER OF FASTENERS PER CONNECTION
PILE TO CAP BEAM	1" DIAM HEX BOLT AND NUT, HDG W/ WASHERS, GRADE 2	2
BLOCKING CONNECTIONS	GRK RUGGED STRUCTURAL SCREW 5/16" X 6" W/ WASHERS	3
DECKING TO JOIST	GRIPE RIGHT 3" X #9 WOOD CONSTRUCTION SCREW W/ PREDRILLING TIP, PRIMEGUARD PLUS COATING	2
POST TO RIM JOIST	3/4" DIAM HEX BOLT AND NUT, HDG W/ WASHERS, GRADE 2	2
BOARDWALK TO BRIDGE	(2) 7 GA. x 6" x 3" GALVANIZED STEEL ANGLE BRACKET W/ 1/2" DIAM HEX BOLTS AND NUTS, HDG W/ WASHERS, GRADE 2	SEE CONNECTION DETAILS
RAILING CONNECTIONS	SEE RAILING DETAILS FOR QUANTITY AND FASTENER TYPE	SEE RAILING DETAILS
STEEL STRAPS	10 GA. x 1" x 12" GALVANIZED STEEL PLATE W/ (6) GRIPE RIGHT #8 X 1 1/4" WOOD CONSTRUCTION SCREW W/ PREDRILLING TIP, PRIMEGUARD PLUS COATING	6

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901


DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO		
ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41


SHEET TITLE:		REF. DWG. NO.
BOARDWALK FRAMING PLAN		
PROJECT NAME:		SHEET NO.
ESTERO ON THE RIVER PEDESTRIAN BRIDGE		25

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


12/27/2023 12:27:32 PM S:\projects\22213_EsteroRiverPedBridge\Structures\AbutmentEndTransition.dgn




END WALL NO. 1 PLAN



SECTION A-A
TYPICAL SECTION ALONG GRAVITY WALL ABUTMENT



END WALL NO. 2 PLAN



SECTION B-B
TYPICAL SECTION AT BEGIN AND END BOARDWALK

- NOTES:
1. COMPACT THE SOIL BENEATH RETAINING WALL EXCAVATION WITH SUITABLE EQUIPMENT TO A DENSITY NOT LESS THAN 95% OF THE MAXIMUM DENSITY AS DETERMINED BY FM 1-T180, FOR A MINIMUM DEPTH OF 2 FEET BELOW THE BOTTOM OF EXCAVATION BEFORE BACKFILLING BEGINS. PROVIDE CLEAN BACKFILL UP TO 6" BELOW THE FINISH GRADE WITHIN THE RETAINING WALL VOLUME.

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
PRELIMINARY NOT FOR CONSTRUCTION					

THOMAS M. WAITS, P.E.
P.E. LICENSE NUMBER 55460
HIGHSPANS ENGINEERING, INC.
2121 MCGREGOR BOULEVARD
SUITE 200
FORT MYERS, FL 33901

DRAWN BY:
JAH 09/23
CHECKED BY:
TMW 09/23
DESIGNED BY:
JAH 09/23
CHECKED BY:
TMW 09/23

VILLAGE OF ESTERO

ROAD NO.	COUNTY	CONTRACT NO.
-	LEE	EC2022-41

SHEET TITLE:

ABUTMENT END TRANSITION

PROJECT NAME:

ESTERO ON THE RIVER PEDESTRIAN BRIDGE


REF. DWG. NO.

SHEET NO.


26

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

12/27/2023 12:27:33 PM S:\projects\22213_EsteroRiverPedBridge\Structures\AbutmentEndWall\Profile.dgn



END WALL NO. 1 ELEVATION
LOOKING AHEAD STATION
(WALL RAILINGS OMITTED FOR CLARITY)




END WALL NO. 2 ELEVATION
LOOKING AHEAD STATION
(WALL RAILINGS OMITTED FOR CLARITY)

REVISIONS						THOMAS M. WAITS, P.E. P.E. LICENSE NUMBER 55460 HIGHSPANS ENGINEERING, INC. 2121 MCGREGOR BOULEVARD SUITE 200 FORT MYERS, FL 33901	DRAWN BY: JAH 09/23 CHECKED BY: TMW 09/23 DESIGNED BY: JAH 09/23 CHECKED BY: TMW 09/23	VILLAGE OF ESTERO			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION						ABUTMENT END WALL ELEVATION		
								ROAD NO.	COUNTY	CONTRACT NO.	PROJECT NAME:		SHEET NO.
								-	LEE	EC2022-41	ESTERO ON THE RIVER PEDESTRIAN BRIDGE		27


PRELIMINARY
NOT FOR CONSTRUCTION

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

10/6/2022 1:34:36 PM



KEYWAY & WALL JOINT DETAIL
(TOP VIEW)




TYPICAL SECTION
C-I-P CONCRETE GRAVITY WALL

ESTIMATED QUANTITIES FOR C-I-P WALL					
HEIGHT (FT.)	PER LINEAR FOOT OF WALL				WEEP HOLES & DRAIN REQD.
	CLASS NS CONCRETE (CY)			REINF. STEEL (LB.)	
	SCHEME 1	SCHEME 2	SCHEME 3 **		
1'	0.08	0.11 (0.20*)	0.03	3 (4*)	No
2'	0.14	0.20 (0.32*)	0.09	4 (5*)	No
3'	0.22	0.32 (0.47*)	0.29	5 (6*)	Yes
4'	0.32 (0.43*)	0.47 (0.65*)	0.43	6 (7*)	Yes
5'	0.43 (0.55*)	0.65 (0.85*)	0.60	7 (8*)	Yes


ESTIMATED QUANTITIES NOTES:
For Scheme 3 Junction Slab and Traffic Railing see the referenced Index for estimated quantities.
* Quantity for 2'-0" Toe Depth.
** Quantity for Scheme 3 assumes 1'-3" thick coping above Gravity Wall.

GENERAL NOTES


- C-I-P Gravity Walls constructed as extensions of reinforced concrete retaining walls, except walls of proprietary designs, shall have the same face texture and finish as the reinforced concrete retaining wall.
- Concrete for Gravity Wall shall be Class NS per Section 347. Concrete for Scheme 3 Junction Slab and Traffic Railing shall be Class II per Section 346, unless otherwise specified in the plans.
- Reinforcing steel shall meet the requirements of Specification Section 931 (Grade 40 or 60). Smooth or Deformed Welded Wire Reinforcement (WWR) may be substituted on an equal area basis. Do not increase bar/wire spacing for Grade 60 reinforcing steel or WWR.
- When required, for adjunct guiderail, see Index 515-070 or 515-080 as appropriate. For adjunct Type B fence see Index 550-002.
- Joint Seal: Organic Felt bond breaker in accordance with Specification Section 400 or Type D-5 geotextile fabric in accordance with Specification Section 985. Mop all contact surfaces of concrete and Organic Felt or geotextile fabric with cut-back asphalt. Stop Organic Felt or geotextile fabric 6" below top of wall.
- Provide a continuous 1'x1' clean gravel or crushed rock drain for wall heights 3 ft. and higher. Wrap drainage layer as shown, with Type D-3 geotextile fabric in accordance with Specification Section 985. Provide 8"x8" galvanized mesh with 1/4" openings, at the inside end of the PVC Drain Pipe. Provide 2" Ø PVC Drain Pipe (Sch. 40) at 10 ft. max. spacing (when Drainage Layer is required). Locate outermost edge of Drain Pipe a minimum of 2'-0" from wall joints.
- Cost of reinforcing steel, face texture, finish, joint seal, drain pipes, drainage layer, galvanized mesh and geotextile fabric to be included in the Contract Unit Price for Concrete Class NS, Gravity Wall. Cost of concrete for Junction Slab in Scheme 3, to be included in Contract Unit Price for Concrete Traffic Railing Barrier With Junction Slab. Adjunct railings or fences to be paid for separately.



SCHEME 1
(No Traffic Loading Effects &
Upper Slopes ≤ 1:1 1/2)



SCHEME 2
(With Traffic Loading or
Upper Slopes > 1:1 1/2)



SCHEME 3
(With Traffic Railing)

BILL OF REINFORCING STEEL		
MARK	SIZE	LENGTH
A	4	As Req'd.
B	4	As Req'd.
BAR BENDING DIAGRAM		
<p>Diagram showing the bar bending diagram for Scheme 3, Scheme 1 & 2. It includes dimensions for wall joint spacing (4" (29'-8" Max.)), bar A dimensions (Height + Toe Depth - 9", Height + Toe Depth - 2'-0"), and bar B dimensions (Height + Toe Depth - 2'-0").</p>		
<p>NOTES: 1. All bar dimensions are out to out. 2. Lap splices for Bars A must be a minimum of 1'-10".</p>		

LAST REVISION 11/01/17	REVISION	DESCRIPTION:	FDOT FY 2023-24 STANDARD PLANS	GRAVITY WALL	INDEX 400-011	SHEET 1 of 1
------------------------------	----------	--------------	--------------------------------------	--------------	------------------	-----------------